



# Staticide® Low-Lint Wipes

## Excellent Value for Industrial Cleaning

ACL Staticide® Low-Lint Wipes provide an economical value for all-purpose cleaning in industrial environments. Soft and strong with outstanding absorbency, these low-particle wipes hold liquid without breaking down or causing lint contamination.

Comprised of a hydroentangled blend of cellulose and polyester fibers, this nonwoven material uses no binders and exhibits lower particle and fiber release than other comparable products. While the polyester lends durability and cleanliness, the cellulose fibers provide excellent sorbency. The robust fiber blend allows chemical solvents like isopropyl alcohol to be absorbed without damaging the fabric, making this all-purpose cleaning wipe an indispensable staple.

These wipes are available in various sizes to suit a wide array of applications. The 9" x 9" wipe is available in white or blue. The blue wipes are non-bleeding and can be used for indicating fluid exposure and for segregating.

### Physical Properties:

Basis Weight: 68 g/m<sup>2</sup> (± 5g/m<sup>2</sup>)

Material: 45% Polyester/ 55% Cellulose

Absorbency: Extrinsic Capacity: >280 ml/m<sup>2</sup>  
Intrinsic Capacity: >4 ml/g  
Sorbptive Rate: <1 second

Test Method: IEST 4.3 Section 8.1

### Product# 8044

6" x 6" / 75 wipes per bag / 12 bags per case

### Product# 8067

4" x 4" / 20 wipes per bag / 24 bags per case

### Product# 8099

9" x 9" / 100 wipes per bag / 6 bags per case

### Product# LF99B (blue)

9" x 9" / 300 wipes per bag / 6 bags per case

### Ideal for the following applications:

- Spill pickup in controlled environments
- Cleaning with IPA and other mild solvents
- Wet applications
- Suitable for ISO Class 6 (Class 1000) environments
- Using with ACL Staticide products such as anti-static topicals, 6001 Mat & Table Top Cleaner, and 8040 Anti-Glare Screen Cleaner

### FEATURES:

- ❄ Hydroentangled nonwoven
- ❄ Binder-free; no chemical residue
- ❄ Low particle and fiber generation
- ❄ Thickness: 68 g/m<sup>2</sup>
- ❄ High liquid absorbency
- ❄ Maintains strength in wet applications

