

TEROSON VR 40

January 2018

PRODUCT DESCRIPTION

TEROSON VR 40 provides the following characteristics:

Technology	Cleaner and Thinner for Bonding and Sealing Applications
Base	Ethyl Acetate

TEROSON VR 40 a liquid cleaner and thinner based on ethyl acetate. Specific care should be exercised when cleaning painted surfaces (especially fresh paint). TEROSON VR 40 will attack painted surfaces when left on the surface for too long. Very short soaking times are recommended.

Application Areas:

TEROSON VR 40 is mainly used for diluting TEROSON-Transparent, Fluid and Universal Adhesive, when required and for removing excess material of these products.

The product is recommended for surface preparation prior to bonding rubber substrates (SBR, NR and NBR). The product can also be used as cleaner for surface preparation prior to bonding and sealing on all substrates (specific care for painted surfaces, see above).

TECHNICAL DATA

(Typical Test Results)

Colour:	clear, transparent
Odour	fruity
Consistency	liquid
Density	0.9 g/cm ³

PRELIMINARY STATEMENT:

Prior to use it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application:

Depending on the degree of contamination and size and shape of the parts to be cleaned, TEROSON VR 40 is applied and wiped off either by brush, cloth, cleaning fleece or similar.

To avoid contamination of the product in the container, TEROSON VR 40 should be either poured onto the brush, cloth, etc. or poured into a different, suitable container.

Dispense only the required amount.

The container should be tightly closed immediately after dispensing.

The cleaner should be allowed to entirely flash-off of the substrate surface (depending on ambient conditions ca. 2 to 10 minutes) before adhesive/sealant application.

With the aid of clean, oil free compressed air, the flash-off time can be reduced.

On porous substrates, a minimum flash-off time of 30 minutes should be observed.

Storage:

Frost sensitive	no
Recommended storage temperature	15 to 25 °C
Shelf life	12 months

Classification:

Please refer to the corresponding **Safety Data Sheets** for details on:

Hazardous Information

Transport Regulations

Safety Regulations

Disclaimer**Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference **N/A**