

TEROSON® VR 5080™

Known as LOCTITE® Teroson® 5080™
July 2015

PRODUCT DESCRIPTION

TEROSON® VR 5080™ provides the following product characteristics:

Technology	Tape
Chemical Type	Synthetic Rubber
Appearance	Metallic gray
Cure	Non-curing
Application	Fix & Repair Tape
Key Substrates	Most surfaces

TEROSON® VR 5080™ is a multi-purpose adhesive tape ideal for repairing, reinforcing, fixing, sealing and protecting parts. Suitable for most surfaces. The tape incorporates a 3-layer technology consisting of 1) a synthetic rubber adhesive layer, 2) an integrated fabric layer and 3) a waterproof layer of polyethylene. Suitable for indoor and outdoor application.

TYPICAL PROPERTIES

Total Thickness, µm	226
Width, mm	50
Length, m	25 or 50
Core, mm	76.2

TYPICAL PERFORMANCE

Tensile Strength, EN 1940	N/cm	42
	lb/in	3.7
Adhesion to steel, EN 1939	N/25mm	43.5
	lb/in	9.9
Rolling ball, PSTC 6	cm	0
	in	0
Shear Resistance @ 22 °C, ASTM D 3654, hours		>168

TYPICAL ENVIRONMENTAL RESISTANCE

Leakage Stop Performance

Emergency stop of leakages in pipes up to 4 bar pressure for minimum 1 hour at 22 °C. Test results measured at steel pipe with a hole of 3 mm, covered by a single layer of TEROSON® VR 5080™.

Not recommended for permanent repair of leakages.

GENERAL INFORMATION

For safe handling information on this product, consult the Safety Data Sheet (SDS).

Directions for use:

The tape can be torn easily and neatly by hand. Ensure that surfaces are clean, free of grease and dry.

For maximum adhesion and durability, press the tape firmly to the bonding surface. If necessary apply more layers.

For best results, use at an ambient temperature.

Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

Storage

Store product in a cool dry place away from direct sunlight and heat sources. **Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.** Henkel Corporation cannot assume responsibility for product which has been stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Conversions

(°C x 1.8) + 32 = °F
kV/mm x 25.4 = V/mil
mm / 25.4 = inches
µm / 25.4 = mil
N x 0.225 = lb
N/mm x 5.71 = lb/in
N/mm² x 145 = psi
MPa x 145 = psi
N·m x 8.851 = lb·in
N·m x 0.738 = lb·ft
N·mm x 0.142 = oz·in
mPa·s = cP

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal

injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1.1