

TEROSON WX 990

Known as Protective Wax

May 2014

PRODUCT DESCRIPTION

TEROSON WX 990 provides the following product characteristics:

Application	Protective Wax
Technology	Anti-Rust Agent in a Spray Can
Basis	Wax

TEROSON WX 990 is a wax-based anti-rust agent in a spray can. When fully dry, Protective Wax forms a durable, non-peeling, water-repellent film. Because the flow point of the dry material is above 100°C there will be no running or dripping even in engine compartments. The dry film adheres well to bare and painted sheet steel.

APPLICATION AREAS

TEROSON WX 990 is used for the protection of seams, surfaces and cavities in motor vehicles, construction machinery, agricultural implements and equipment for the home and garden. Because of its light colour, it is particularly suitable for use in motor vehicles for the protection of seams on bonnets and in boots. The material is also highly suitable for protecting cleaned engine compartments.

TECHNICAL DATA

(Typical Test Results)

Colour	translucent
Odour	slight characteristic odour
Density	approx. 0.78 g/cm ³
Solids	16 %
Viscosity (DIN 53211, 4 mm)	12 to 14 s
Drop point of solid (DIN 51801)	100 °C
Cleaning	with white spirit, Cold Cleaner or petroleum
Application temperature	15 to 30 °C

PRELIMINARY STATEMENT

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Pretreatment

Parts which are to be treated with TEROSON WX 990 should first be thoroughly cleaned and dried. Any rust should be removed.

Application

Shake the can well before use. Spray TEROSON WX 990 as required and allow to dry. TEROSON WX 990 should not be sprayed onto visible exterior surfaces as the dry film produces a matt appearance. When treating the engine compartment, care should be taken to ensure that it is not only dry but also cold (see application temperature).

After treating engine compartments in motor vehicles and motors in other equipment and machines, the engine/motor should not be switched on until the protective wax film has been thoroughly aired. (Explosion hazard through evaporating solvent!)

STORAGE

Frost sensitive	no
Recommended storage temperature	10 to 20 °C; (never heat above 50 °C!)
Shelf life	18 months

Disclaimer**Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is

TEROSON**TEROSON WX 990**

Known as Protective Wax

May 2014

excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel AG & Co. KGaA

D-40191 Düsseldorf, Germany

Phone: +49-211-797-0

www.henkel.com

Henkel Central Eastern Europe GmbH

A-1030 Wien, Austria

Phone: +43-1711-040

www.henkel.com

Henkel & Cie AG

CH-4133 Pratteln, Switzerland

Phone: +41-61-825-7000

www.henkel.com

